



## MV 50X



Chamber & Seal Bars	
Chamber Width x Length	26" x 20.5"
Height (Chamber + Dome/Lid = Total)	5" + 4" = 9"
Number of Seal Bars	2
Position of Seal Bars	Left & Right
Seal Bar Length	2 x 20.25"
Distance between Seal Bars	22"
Seal: Flat (4mm) + Bag Trimmer	✓
Unique Waffle-Pattern Sealing	✓
Pop-Out Seal Bars	✓
Independent Power to each Seal Bar	✓
Performance	
Pump Type	Busch R5 Oil Rotary
Cycles per Minute*	up to 3
Free Air Displacement	40 m <sup>3</sup> /h
Pump Power Rating	2 hp
Power Supply	208V / 3ph / 14A
Display & Controls	
Water Resistant Digital Display	✓
LED Full Description Display	✓
Electronic Millibar Sensor	✓
Customizable Programs	9
Operational Features	
Programmable Sealing Time	✓
Programmable Vacuum Time (%)	✓
Moisture Quick Stop	✓
Excess Bag Cut-Off	✓
High Volume Density Plates	✓
Service	
Indicating Display	✓
Programmable Service Reminder	✓
1 Year Limited Warranty	✓
Housing & Dimensions	
Material	Stainless 304
Lid Type	Transparent with Dome
Width x Length	31" x 29"
Height (Lid open/closed)	51.75" / 40.5"
Working Height	35"
Locking Casters	✓
Shipping Wt.	450lbs
Certificates	
ETL Electrical	 Electrical Approved
ETL Sanitation (NSF Standard)	 Sanitation Approved
Optional Seal Bars	
Liquid & Foil Bag Seal	✓
Optional Features	
Tray for Liquid	✓
Gentle Air Return	✓
Inert Gas Kit (4 Nozzles)	✓
220V / 1ph / 16.5A / 40 m <sup>3</sup> /h	✓

\*Depends on type of product, film and operator ability. Specifications may change without notice.