



MV 65X



| Chamber & Seal Bars | |
|--|---|
| Chamber Width x Length | 29" x 27" |
| Height (Chamber + Dome/Lid = Total) | 5" + 5.5" = 10.5" |
| Number of Seal Bars | 2 |
| Position of Seal Bars | Left & Right |
| Seal Bar Length | 2 x 26" |
| Distance between Seal Bars | 24" |
| Seal: Flat (4mm) + Bag Trimmer | ✓ |
| Unique Waffle-Pattern Sealing | ✓ |
| Pop-Out Seal Bars | ✓ |
| Independent Power to each Seal Bar | ✓ |
| Performance | |
| Pump Type | Busch R5 Oil Rotary |
| Cycles per Minute* | up to 3 |
| Free Air Displacement | 63 m ³ /h |
| Pump Power Rating | 3 hp |
| Power Supply | 208V / 3ph / 19A |
| Display & Controls | |
| Water Resistant Digital Display | ✓ |
| LED Full Description Display | ✓ |
| Electronic Millibar Sensor | ✓ |
| Customizable Programs | 9 |
| Operational Features | |
| Programmable Sealing Time | ✓ |
| Programmable Vacuum Time (%) | ✓ |
| Moisture Quick Stop | ✓ |
| Excess Bag Cut-Off | ✓ |
| High Volume Density Plates | ✓ |
| Service | |
| Indicating Display | ✓ |
| Programmable Service Reminder | ✓ |
| 1 Year Limited Warranty | ✓ |
| Housing & Dimensions | |
| Material | Stainless 304 |
| Lid Type | Transparent with Dome |
| Width x Length | 32" x 35" |
| Height (Lid open/closed) | 58.25" / 41.25" |
| Working Height | 35" |
| Locking Casters | ✓ |
| Shipping Wt. | 580lbs |
| Certificates | |
| ETL Electrical |  ETL Electrical Approved |
| ETL Sanitation (NSF Standard) |  ETL Sanitation Approved |
| Optional Seal Bars | |
| Liquid & Foil Bag Seal | ✓ |
| Optional Features | |
| Tray for Liquid | ✓ |
| Gentle Air Return | ✓ |
| Inert Gas Kit (4 Nozzles) | ✓ |
| 220V / 1ph / 22A / 63 m ³ /h | ✓ |
| 208V / 3ph / 18A / 100 m ³ /h | ✓ |

*Depends on type of product, film and operator ability.
 Specifications may change without notice.