

9130 UTENSIL WASHER Technical specification



POWER / CONNECTIONS

Electrical

Electrical connection 3N 60Hz 240/480, PE Effect 16.5 kW

Heating Elements

Wash tank 1x4.5 kW Rinse Tank 2x6.0 kW

Fuses

240 volt Max 50 amp 480 volt Max 50 amp

Wash pump motor horsepower 2-2.7 kW

Water

Connection ½ inch.

Pressure 45 to 60 psi

Consumption per cycle 1.5 gallons

Temperature: (minimum) 122° F (50 C°)

Drain

Drain dimension: 1 ½ inch

Rinse Temperature: 183° F (84° C) Rinse Time: 25 seconds

Standard Features

- 4 sided moving wash frame
- Load and unload from 3 sides
- Self cleaning program
- Adjustable wash temperature
- Hi and low wash programs
- 3 preset programs 2, 4, 6 min.
- 2 easily accessible filters
- 2-2.7 kW wash pumps
- 21 psi of pressure at the nozzle
- Automatic start
- Drain pump
- Soap dosage pump

Optional features

- Automatic hood opener
- Chemical sanitizer pump
- Integrated faucet
- External pre-wash hose
- Side table
- Pre-wash table with sink

General specification

Wash tank capacity 33 gallons

Wash area

 $H \times W \times D$ 25x50x27 inch

Overall dimensions

H x W x D 64x57x31 inch H x W x D with hood open 82x57x31 inch

Weight Shipping 550 lbs

Weight installed (Including Water) 825 lbs

Water connection, flexible 8 feet
Electrical connection 8 feet

Vinyl brush, daily maintenance 1 piece



ALL SPECIFICATION SUBJECT TO CHANGE WITHOUT NOTICE